MATERIAL SAFETY DATA SHEET

January 3, 2014

MSDS ID# THE PUMPER PUMP ACTION MARKER INK - WHITE

PRODUCT NAME: XYLENE BASED PUMP ACTION MARKER INK - WHITE

PART #: 39-68-A3

SECTION I SUPPLIER INFORMATION

COMMON NAME: XYLENE BASED PUMP ACTION MARKER INK - WHITE

CHEMICAL NAME: N/A FORMULA/CAS: N/A

SUPPLIER: GENPACK INDUSTRIES LTD.

ADDRESS: 143 HUGGARD ROAD

CITY, STATE, ZIP: CALGARY, ALBERTA, CANADA T3Z 2C2

TOLL FREE: 888-657-3030 PH: 403-266-4363

DATE ISSUED: 01-03-14 DATE ENTERED: 01-03-14

DATE REVISED: 01-03-14

SECTION II INGREDIENT INFORMATION

XYLENE CAS#: 1330-20-7 %: 35 - 50

OSHA PEL: 100 PPM TLV-ACGIH: 100 PPM

NON-HAZARDOUS INGREDIENTS:

PIGMENT WHITE 6 CAS#: 13463-67-7 %: 35 - 50
RESIN CAS#: 68132-02-5 %: 10 - 15
PROPRIETARY SURFACTANT CAS#: MIXTURE %: < 1

THIS PRODUCT IS REPORTABLE UNDER THE S.A.R.A. ACT OF 1986, TITLE III, SEC. 313 (40 CFR PART 372) DUE TO THE PRESENCE OF THE INGREDIENT(S) CITED ABOVE.

THIS PRODUCT DOES NOT CONTAIN ANY KNOWN CHEMICAL REPORTABLE UNDER THE CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT OF 1986. (CA PROP 65).

THIS PRODUCT CONTAINS NO CARCINOGENS OR REPRODUCTIVE CHEMICALS AS LISTED BY NTP, IARC, OR OSHA. THIS PRODUCT MEETS THE CONEC LEGISLATION.

ALL INGREDIENTS MEET TSCA REQUIREMENTS

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT : $279^{\circ}F$ SPECIFIC GRAVITY (H20 = 1) : 1.235

MELTING POINT : NOT ESTABLISHED VAPOR PRESSURE (mm HG) : 2.4 mmHg @ 68°F VAPOR DENSITY (AIR = 1) : APPROX. 3.66 EVAPORATION RATE (BUTYL ACETATE=1) : APPROX. 0.86 SOLUBILITY/WATER : LESS THAN 0.08%

WHITE LIQUID WITH SLIGHT AROMATIC ODOR

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : APPROX. 80°F (26.6°C) TCC

AUTO IGNITION : 980°F LEL : 1.0% UEL : 6.6%

FLAMMABLE: 3 HEALTH: 1 REACTIVITY: 0 SPECIAL: 0

WARNING: FLAMMABLE

CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

SECTION V REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

AVOID : HEAT, SPARKS, FLAMES

STRONG OXIDIZING AGENTS.

POLYMERIZATION: POLYMERIZATION WILL NOT OCCUR

AVOID : NONE

SECTION VI HEALTH HAZARD DATA

INHALATION :YES SKIN :YES INGESTION :YES EYES :YES

CONTACT PERSON: MICHAEL J MARTIN

PRESIDENT

NTP: NO IARC: NO OSHA: NO

*****MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE***********
INHALATION OF HIGH CONCENTRATIONS OF THIS MATERIAL, AS COULD
OCCUR IN ENCLOSED SPACES OR DURING DELIBERATE ABUSE, MAY BE
ASSOCIATED WITH CARDIAC ARRHYTHMIAS. SYMPATHOMIMETIC DRUGS MAY
INITIATE CARDIAC ARRHYTHMIAS IN PERSONS EXPOSED TO THIS MATERIAL.

INHALATION: REMOVE TO FRESH AIR. SEEK MEDICAL ATTENTION AS

NEEDED.

EYES: IMMEDIATELY FLUSH WITH WATER CONTINUOUSLY FOR AT

LEAST 15 MINUTES. SEEK MEDICAL ATTENTION AS

NEEDED.

SKIN: REMOVE CONTAMINATED CLOTHING AND WASH EXPOSED SKIN

WITH SOAP AND WATER. SEEK MEDICAL ATTENTION AS

NEEDED FOR HYPERSENSITIVITY.

INGESTION: DO NOT INDUCE VOMITING. THIS MATERIAL IS AN

ASPIRATION HAZARD. CALL PHYSICIAN AND SEEK MEDICAL ATTENTION PROMPTLY. TREAT FOR THE PRESENCE OF INGREDIENT(S) CITED IN SECTION II.

SECTION VII

PRECAUTIONS FOR SAFE HANDLING AND USE

DOT CLASSIFICATION: FLAMMABLE LIQUID

****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**** SOAK UP SPILL WITH INERT MATERIAL SUCH AS; VERMICULITE, DRY CLAY ABSORBENT OR CHEMSORB. WIPE UP SMALL SPILLS WITH A CLOTH OR TOWEL. PREVENT RUN-OFF FROM ENTERING DRAINS, SEWERS OR RIVERS.

WASTE DISPOSAL SHOULD BE IN ACCORDANCE WITH EXISTING FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS

******PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE******** STORE IN COOL, DRY AREA. AVOID FREEZING, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE.

WEAR SAFETY GOGGLES AT ALL TIMES WHEN USING THIS LIQUID TO AVOID THE POSSIBILITY OF SPLASHING IN THE EYES.

SECTION VIII CONTROL MEASURES

****************RESPIRATORY PROTECTION********************* NONE REQUIRED

LOCAL EXHAUST : AS NEEDED

: NONE SPECIAL EXHAUST MECHANICAL EXHAUST : NONE

: CHEMICAL RESISTANT

EYE PROTECTION : CHEMICAL SAFETY GOGGLES

IMPERMEABLE APRON TO PREVENT THE STAINING OF CLOTHES.

ALWAYS WASH THOROUGHLY AFTER HANDLING PRODUCT AND BEFORE EATING, DRINKING, SMOKING OR USING THE RESTROOM.

THIS IS THE END OF THE MSDS ID # XYLENE BASED PUMP ACTION MARKER INK - WHITE 39-68-A3